



## TECHNICAL FACT SHEET

	AQUILA 18	AQUILA 20	AQUILA 22	
CLASSIFICATION EN	–	D	D	
AREA FLAT (m <sup>2</sup> )	18	20	22	
AREA PROJECTED (m <sup>2</sup> )	9,6	10,1	10,6	
WINGSPAN FLAT (m)	15,2	17	18,7	
WINGSPAN PROJECTED (m)	7,6	8	8,4	
ASPECT RATIO FLAT	5,1	5,1	5,1	
ASPECT RATIO PROJECTED	3,8	3,8	3,8	
CARABINER DISTANCE	< 80 Kg: 38-42 cm	80-100 Kg: 42-46 cm	> 100 Kg: 46-50 cm	
WEIGHT (Kg)	4,4	4,5	4,7	
PROFILE TYPE	THERMAL	THERMAL	THERMAL	
MATERIALS	DOKDO 30	DOKDO 30	DOKDO 30	
NUMBER OF CELLS	36	36	36	
V-TAPE TYPE	2-CELL-BRIDGE	2-CELL-BRIDGE	2-CELL-BRIDGE	
MINI RIBS	YES	YES	YES	
LINE GEOMETRY	3 + 1	3 + 1	3 + 1	
SPEED SYSTEM	YES	YES	YES	
SPEED WAY (mm)	80	80	80	
TRIMMER	NO	NO	NO	
V TRIM (Km/h)	–	–	–	
V MAX (Km/h)	–	–	–	
SEATS	1	1	1	
INSPECTED BY	EAPR GMBH / MARKTSTR. 11 / 87730 BAD GRÖNENBACH / GERMANY			
TEST REFERENCE NR.	–	–	–	
TEST REGULATIONS	EN 926-1:2006 / LTF 91/09	EN 926-2:2013 / EN 926-1:2006 / LTF 91/09 NFL 2-60-14		

STATE: Juli 2015

